

NORLOK EZ CLINCH™

Norlok is connecting with the RIDGID® QuickChange System™, providing a battery powered clinching tool that can be carried anywhere in the shop and on the jobsite.



The RIDGID logo is a registered trademark, and QuickChange System is a trademark, of RIDGID, Inc. in the U.S. and other countries

- Single hand operation makes it easier to clinch in tough spots
- With a 5/8" throat and 3/8" opening, the EZ Clinch™ can get over the flange to make your part
- Full rotation of clinching head and inline design provides new clinching capabilities
- Capable of clinching up to two layers of .050" aluminum or up to two layers of 16-gauge galvanized steel



EZ Clinch™ integrates with the RIDGID® RE 6

INNOVATIONS IN ENGINEERING

EZ CLINCH™



Model: 6340
Cycle Time: 7 cycles per minute
Opening: 0.40"/10.1mm
Tool Mass (Tool Only): 4.5lbs/2.0kg
Tool Mass (Connected to RIGID RE6): 10.0lbs/4.5kg

Minimum sheet metal thickness:
Two sheets 0.022"/0.56mm steel
Two sheets 0.024"/0.61mm aluminum
Maximum sheet metal thickness:
Combined thickness 0.120"/3.0mm steel
Combined thickness 0.090"/2.3mm aluminum

