

NORLOK EZ CLINCH™

Norlok is connecting with the RIDGID® QuickChange System™, providing a battery powered clinching tool that can be carried anywhere in the shop and on the jobsite.



- Single hand operation makes it easier to clinch in tough spots
- With a 1.5" throat and 0.4" opening, the EZ Clinch™ can get over the flange to make your part
- Full rotation of clinching head and inline design provides new clinching capabilities
- Capable of clinching up to two layers of .050" aluminum or up to two layers of 16-gauge galvanized steel

The RIDGID logo is a registered trademark, and QuickChange System is a trademark, of RIDGID, Inc. in the U.S. and other countries



EZ Clinch™ integrates with the RIDGID® RE 6

INNOVATIONS IN ENGINEERING

EZ CLINCH™



Model: 15040

Cycle Time: 7 cycles per minute

Opening: 0.40"/10.1mm

Tool Mass (Tool Only): 7.4lbs/3.4kg

Tool Mass (Connected to RIGID RE6): 12.9lbs/5.9kg

Minimum sheet metal thickness:

Two sheets 0.022"/0.56mm steel

Two sheets 0.024"/0.61mm aluminum

Maximum sheet metal thickness:

Combined thickness 0.120"/3.0mm steel

Combined thickness 0.090"/2.3mm aluminum

