

# NORLOK EZ CLINCH™

Norlok is connecting with the RIDGID® QuickChange System™, providing a battery powered clinching tool that can be carried anywhere in the shop and on the jobsite.



- Single hand operation makes it easier to clinch in tough spots

With a 3.25" throat and 0.4"

- opening, the EZ CLINCH™ can get over the flange to make your part
- Full rotation of clinching head and inline design provides new clinching capabilities
- Capable of clinching up to two layers of .050" aluminum or up to two layers of 16-gauge galvanized steel

The RIDGID logo is a registered trademark, and QuickChange System is a trademark, of RIDGID, Inc. in the U.S. and other countries



EZ CLINCH™ integrates with the RIDGID® RE 6

**INNOVATIONS IN ENGINEERING**

# EZ CLINCH™



Model: 32540

Cycle Time: 7 cycles per minute

Opening: 0.40"/10.1mm

Tool Mass (Tool Only): 14.9lbs/6.8kg

Tool Mass (Connected to RIGID RE6): 20.4lbs/9.3kg

Minimum sheet metal thickness:

Two sheets 0.022"/0.56mm steel

Two sheets 0.024"/0.61mm aluminum

Maximum sheet metal thickness:

Combined thickness 0.120"/3.0mm steel

Combined thickness 0.090"/2.3mm aluminum

